

SUGGESTED CONSTRUCTION SEQUENCING (*note to designer: edit as needed to meet project requirements*)

1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 feet of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (*note to designer: edit as needed to meet project requirements*)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS


1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

NO.	REVISION DESCRIPTION	DATE	BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.

Print Name: _____
 Sign Name: _____
 Date: _____ License No.: _____

Date _____
 Designed By _____
 Drawn By _____



Note: in offline systems, when flow exceeds the volume available in the bioretention ponding area, all additional flow bypasses the bioretention facility and continues to flow downstream

Bioretention Plan - Offline

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Sheet No. _____ of _____
 Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)

1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 foot of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS


1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

NO.	REVISION DESCRIPTION	DATE BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.

Print Name: _____
Sign Name: _____
Date _____ License No. _____

Date	Designed By	Drawn By



Note: in on line systems, when flow exceeds the volume available in the bioretention ponding area, all additional flow enters the overflow structure (set at maximum ponding elevation) and flows through the bioretention facility

Bioretention Plan - On Line

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Sheet No. _____ of _____
Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)


1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 foot of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.



Not To Scale

NOT FOR CONSTRUCTION PURPOSES

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	NO.	REVISION DESCRIPTION	DATE							
	Date	Designed By	Print Name	Drawn By	Sign Name	Date	License No.			
Sheet No.		of								
		Sheets								

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)

1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 foot of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.


GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

Note: this detail shows an off line system. To show an on line system, this detail should be modified to include an overflow structure, set at the maximum ponding elevation.



Bioretention with Underdrain at Bottom

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Date	Designed By	Drawn By	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	NO.	REVISION DESCRIPTION	DATE	BY

Sheet No. _____ of _____ Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)


1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter erosion control bmps must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 feet of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.


MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.




>= 30" Bioretention Soil
Geogrid Wrap, connected with zip ties
2" Choker Course, #8, #78, or #89 Stone
#57 Stone, Pipe width + 2" Above Pipe

Note: this detail shows an off line system. To show an on line system, this detail should be modified to include an overflow structure, set at the maximum ponding elevation.



Biofiltration with Elevated Underdrain



Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Date	Designed By	Drawn By	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	NO.		REVISION DESCRIPTION	DATE	BY

Sheet No. _____ of _____ Sheets

- SUGGESTED CONSTRUCTION SEQUENCING** (*note to designer: edit as needed to meet project requirements*)
1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
 2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
 3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
 4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
 5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 foot of cover over the practice to protect the underlying soils from clogging.
 6. Complete, stabilize, and vegetate all other site improvements.
 7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
 8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.


GENERAL NOTES (*note to designer: edit as needed to meet project requirements*)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

Note: this detail shows an off line system. To show an on line system, this detail should be modified to include an overflow structure, set at the maximum ponding elevation.



Biofiltration with Internal Water Storage

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

NO.	REVISION DESCRIPTION	DATE	BY

Date _____
 I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota
 Designed By _____
 Print Name: _____
 Drawn By _____
 Sign Name: _____
 Date _____ License No. _____

Sheet No. _____ of _____ Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)

1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 foot of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.


GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

Note: this detail shows an off line system. To show an on line system, this detail should be modified to include an overflow structure, set at the maximum ponding elevation.



Biofiltration with Liner

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Date	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	NO.	REVISION DESCRIPTION	DATE	BY
Designed By	Print Name:				
Drawn By	Sign Name:				
	Date				
	License No.				

Sheet No. _____ of _____ Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)


1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 feet of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.



Biofiltration Planter - Plan

Not To Scale

NO.	REVISION DESCRIPTION	DATE BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota

Print Name: _____ Date: _____
Sign Name: _____ License No.: _____

Date: _____
Designed By: _____
Drawn By: _____

Sheet No. _____ of _____
Sheets

NOT FOR CONSTRUCTION PURPOSES

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)


1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 feet of cover over the practice to protect the underlying soils from clogging.
6. Complete stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.



Biofiltration Planter - Section

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Date	Designed By	Drawn By	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	NO.	REVISION DESCRIPTION	DATE	BY

Sheet No. _____ of _____ Sheets

SUGGESTED CONSTRUCTION SEQUENCING (note to designer: edit as needed to meet project requirements)


1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary/ sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1' feet of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.

GENERAL NOTES (note to designer: edit as needed to meet project requirements)

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.



Bioretention Parking Median-Plan

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

NO.	REVISION DESCRIPTION	DATE	BY	Date	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota
				Designed By	
				Print Name: _____	
				Sign Name: _____	
				Date: _____ License No. _____	

Sheet No. _____ of _____ Sheets

SUGGESTED CONSTRUCTION SEQUENCING *(note to designer: edit as needed to meet project requirements)*

1. Install appropriate temporary erosion control devices to prevent sediment from leaving or entering the practice during construction.
2. All down-gradient perimeter sediment control bmp's must be in place before any up gradient land disturbing activity begins.
3. Perform continuous inspections of erosion control practices, especially after each rainfall event.
4. Install all utilities (water, sanitary sewer, electric, natural gas, phone, fiber optic, etc) prior to setting final grade of bioretention device.
5. Rough grade the site. If bioretention areas are being used as temporary sediment basins during construction, leave a minimum of 1 feet of cover over the practice to protect the underlying soils from clogging.
6. Complete, stabilize, and vegetate all other site improvements.
7. Construct and vegetate bioretention device following stabilization of contributing drainage area. Ensure that critical elevations, such as underdrain invert, top of media, top of mulch, and invert of overflow structure (if present) are correct.
8. Remove temporary erosion control devices after the contributing drainage area is adequately vegetated.


GENERAL NOTES *(note to designer: edit as needed to meet project requirements)*

1. In the event that sediment is introduced into the bmp during or immediately following excavation, this material shall be removed from the practice prior to continuing construction.
2. See Minnesota Stormwater Manual for subgrade preparation.

MATERIAL SPECIFICATIONS

1. See Minnesota Stormwater Manual for material specifications recommendations for bioretention soil, mulch, underdrains, etc.

Note: this detail shows an off line system. To show an on line system, this detail should be modified to include an overflow structure, set at the maximum ponding elevation.



○ Bioretention Parking Median-Section

Not To Scale


NO.	REVISION DESCRIPTION	DATE	BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	Date	Print Name:	Sign Name:	License No.:
	Designed By	Drawn By	Date	

NOT FOR CONSTRUCTION PURPOSES	Sheet No.	of



Cleanout




Not To Scale

NOT FOR CONSTRUCTION PURPOSES

Sheet No. _____ of _____ Sheets

Date	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.	NO.	REVISION DESCRIPTION	DATE BY
Drawn By				



Underdrain Valve

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.		NO.	REVISION DESCRIPTION	DATE BY
Date	Print Name:			
Designed By	Sign Name:			
Drawn By	Date			
	License No.			
Sheet No.		of		
		Sheets		

Biofiltration with Elevated Underdrain

More of the runoff that flows into the basin and does not overflow into an overflow structure is abstracted from the stormsewer system through infiltration or evapotranspiration compared to bioretention with an underdrain at the bottom of the basin; the remainder is filtered by the growing medium but then leaves via an elevated underdrain.

Because elevating the underdrain increases hydraulic retention time, it (1) allows for **more infiltration and evaporation** compared to biofiltration with underdrain at the bottom, but likely some flow short circuits media below underdrain invert, resulting in slightly less volume and water quality benefits than biofiltration with an underdrain with upturned elbow (2) Improves **thermal pollution abatement** and **nitrogen removal** (longer retention time allows runoff to cool more before discharge and allows denitrification to occur under anoxic condition).

With an elevated outlet, biofiltration can be added as retrofits in more areas with restricted outlet depth.

Requires more aggregate than biofiltration with upturned elbow

In-situ soils must have adequate permeability for an elevated underdrain to be beneficial.




Figure 2-3: Biofiltration with Elevated Underdrain

Not To Scale


NOT FOR CONSTRUCTION PURPOSES

		NO.	REVISION DESCRIPTION	DATE	BY
Date	I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota				
Designed By					
Drawn By					
	Print Name:				
	Sign Name:				
	Date:				
	License No.:				

Sheet No. _____ of _____ Sheets

Biofiltration with Internal Water Storage

More of the runoff that flows into the basin and does not overflow into an overflow structure is abstracted from the stormsewer system through infiltration or evapotranspiration compared to biofiltration with an underdrain at the bottom of the basin without an upturned elbow; the remainder is filtered by the growing medium but then leaves via an underdrain with an upturned elbow.



While biofiltration systems have been shown to perform well in some clayey soils, in-situ soils must have adequate permeability for an underdrain with upturned elbow to be beneficial.

Because the upturned elbow increases hydraulic retention time, it (1) allows for **more infiltration and evaporation** compared to bio-retention with underdrain at the bottom; (2) improves **thermal pollution abatement and nitrogen removal** (longer retention time abstracts more stormwater from the storm sewer, allows runoff to cool more before discharge, and allows denitrification to occur under anoxic conditions). Reducing thermal pollution is especially beneficial for temperature reductions in trout waters.

Figure 2-4: Biofiltration with Internal Water Storage

Not To Scale

NO.	REVISION DESCRIPTION	DATE	BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota	
Print Name:	
Sign Name:	
Date	
License No.	

Date	
Designed By	
Drawn By	

NOT FOR CONSTRUCTION PURPOSES

Sheet No.	
of	

Sheets

Biofiltration with Underdrain at Bottom

A small amount of the runoff that flows into the basin and does not overflow into an overflow structure is abstracted from the stormsewer system through infiltration or evapotranspiration; the remainder is filtered by the growing medium but then leaves via an underdrain.




Figure 2-2: Biofiltration with Underdrain at Bottom

Not To Scale

REVISION DESCRIPTION		NO.	DATE BY

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota


Print Name: _____
 Sign Name: _____
 Date _____ License No. _____

NOT FOR CONSTRUCTION PURPOSES

Sheet No. _____ of _____ Sheets

Bioinfiltration

There is no underdrain, so all runoff that flows into the basin and does not overflow into an overflow structure is abstracted from the stormsewer system through infiltration or evapotranspiration.



Since there is no underdrain, in-situ soils must be able to handle discharge through the soil or filter media in 48 hours or less. The period of inundation is defined as the time from the high water level in the practice to 1 to 2 inches above the bottom of the facility



Figure 2-1: Bioinfiltration

Not To Scale

NOT FOR CONSTRUCTION PURPOSES

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota		NO.	REVISION DESCRIPTION	DATE BY
Date	Print Name:			
Designed By	Sign Name:			
Drawn By	Date			
	License No.			
Sheet No.		of		
		Sheets		

Biofiltration with Liner

None of the runoff that flows into the basin is abstracted from the stormsewer system through infiltration but some is abstracted through evapotranspiration; i.e. all of the runoff that flows into the basin without flowing into an overflow structure, and is not evapotranspired, is filtered by the growing medium but then leaves via an underdrain




Figure 2-5: Bioretention with Liner

Not To Scale

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota		NO.	REVISION DESCRIPTION	DATE BY
Date	Print Name:			
Designed By	Sign Name:			
Drawn By	Date			
	License No.			

NOT FOR CONSTRUCTION PURPOSES